

Standard Connections

- BS 799: Part 5: **Type J or K**
- Internally stayed as necessary
- Certified tested
- Fitted with 600mm dia. manhole with set pinned cover and gasket
- Standard connections include two 65mm, one 40mm and one 25mm screwed sockets
- Calibrated dipstick/gauge and other fittings if required
- Manufactured from steel plate to BS EN 10 025: 2004: S275.

- Inclusive of B.S.P screwed bosses to BS 21
- Aboveground tanks finished in two coats of primer or one coat zinc alkyd primer and one coat of oil resistant gloss finish
- Alternatively finished to customers requirements
- Calibrated dipstick, gauge, alarm and other fittings if required.



Rectangular

Ref	Capacity Litres	Length metres	Width metres	Depth metres	Plate Thickness & weight (Approx)Kg		
					3mm	5mm	6mm
R00	1000	1.200	1.200	700	180		
R01	2272	1.524	1.219	1.219	305	432	559
R02	2727	1.829	1.219	1.219	343	483	635
R03	2841	1.905	1.219	1.219	343	495	648
R04	2954	1.981	1.219	1.219	356	508	674
R05	3409	2.286	1.219	1.219	394	572	750
R06	3636	2.438	1.219	1.219	423	598	788
R07	4457	2.438	1.500	1.219	470	686	901
R08	4545	3.048	1.219	1.219	495	686	940
R09	5486	2.438	1.500	1.500	495	711	940
R10	5573	3.048	1.500	1.219	559	812	1051
R11	6858	3.048	1.500	1.500		914	1204
R12	7955	2.438	1.829	1.829		965	1255
R13	9091	3.048	2.438	1.219		1127	1476
R14	8916	2.438	2.438	1.500			1408
R15	11147	3.048	2.438	1.500			1639
R16	13377	3.658	2.438	1.500			1927
R17	13637	3.048	2.438	1.829			1825
R18	18183	3.048	2.438	2.438			2243
R19	22729	3.962	2.438	2.438			2753
R20	27275	3.658	3.048	2.438			3051
R21	31821	4.267	3.048	2.438			3347
R22	36367	4.877	3.048	2.438			3775
R23	40913	5.486	3.048	2.438			4141
R24	45459	6.096	3.048	2.438			4762
R25	54551	6.096	3.048	3.048			5075

